

45V Input Voltage, 2.5uA Ultra-low Iq, 300mA LDO

DESCRIPTION

ETA5040 is a low-dropout (LDO) linear voltage regulator that features ultra-low standby current as low as 2.5uA. It can withstand input voltage up to 48V and deliver 300mA output current.

ETA5040 can provide fixed output voltages with wide input voltage range from 3V to 45V. The device also includes short circuit protection, UVLO and thermal shutdown.

Therefore, ETA5040 is an ideal power supply for low power applications such as IoT, portable and multi-cell battery-powered system, etc.

ETA5040 is housed in a tiny SOT23-5 and DFN1.6x1.6-6 package.


FEATURES

- ◆ Wide Input Voltage Range: from 3V to 45V
- ◆ Ultra-Low Quiescent Current: 2.5uA
- ◆ 300mA Output Current
- ◆ Stable with a Wide Range of Ceramic Capacitor, Larger than 1 μ F
- ◆ High PSRR, 70dB at 1KHz
- ◆ Integrated Thermal and Current Limit
- ◆ SOT23-5 and DFN1.6x1.6-6 Package
- ◆ RoHS Compliant

APPLICATIONS


- ◆ Portable Equipment
- ◆ Multi-cell Battery-Powered System
- ◆ NB-IoT Module

TYPICAL APPLICATION



ORDERING INFORMATION	PART No.	PACKAGE	TOP MARK	Pcs/Reel
	ETA5040V <u>XXX</u> O <u>S2F</u>	SOT23-5	<u>PPYW</u>	3000
	ETA5040V <u>XXX</u> Q <u>DCG</u>	DFN1.6x1.6-6	<u>PPYW</u>	3000
	<u>XXX</u> : Voltage Code e.g. <u>120</u> =1.2V <u>Q=N</u> : no discharge; <u>Q=D</u> : discharge		PP: product code <u>YW</u> : data code	

PIN CONFIGURATION



ABSOLUTE MAXIMUM RATINGS

(Note: Exceeding these limits may damage the device. Exposure to absolute maximum rating conditions for long periods may affect device reliability.)

VIN, EN to GND Voltage	-0.3V to 48V
VOUT to GND Voltage.....	-0.3V to 40V
Operating Temperature Range	-40°C to 85°C
Storage Temperature Range	-55°C to 150°C
Thermal Resistance θ_{JA} θ_{JC}	
SOT23-5.....	220.....110..... °C/W
DFN1.6x1.6-6.....	46.5.....18.6..... °C/W
Lead Temperature (Soldering 10sec)	260°C

ELECTRICAL CHARACTERISTICS

($V_{IN} = V_{OUT} + 1V$, unless otherwise specified. Typical values are at $T_A = 25^\circ C$.)

PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
Input Voltage Range ⁽¹⁾		3	45		V
Ground Current	No Load		2.5		uA
Shutdown Current	$V_{EN}=0V$		1		uA
Dropout Voltage	$I_{OUT}=100mA, V_{OUT}=3.3V$		540		mV
Output Current Limit	$V_{OUT}=95\%$	300	400		mA
Output Foldback Current Limit	$V_{OUT}=0V$		200		mA
Line Regulation	$V_{OUT}+1V \leq V_{IN} \leq 45V$			0.12	%/V
Load Regulation	$1mA \leq I_{OUT} \leq 100mA$		20		mV
Output Voltage Range	Available in 100mV steps	1.2	20		V
Output Voltage Accuracy	$I_{OUT}=30mA$	-2	2		%
Power Supply Rejection Ratio	Freq = 100Hz, $I_{OUT} = 10mA$		88		dB
	Freq = 1KHz, $I_{OUT} = 10mA$		70		dB
EN Logic High Threshold	Rising	1.2			V
EN Logic Low Threshold	Falling		0.4		V
Discharge Resistance ⁽²⁾	$V_{EN}=0$		60		Ω
EN Input Current	$V_{EN}=3V$		0		uA
Thermal Shutdown	Hysteresis=30°C		160		°C

(1): Minimum V_{IN} is 3V or $V_{OUT} + V_{DROPOUT}$, whichever is greater.

(2): This parameter is for output discharge version.



PIN DESCRIPTION

SOT23-5 PIN #	NAME	DESCRIPTION
1	VIN	Supply voltage pin. Bypass with a 1 μ F ceramic capacitor to GND
2	GND	Ground
3	NC	None connection
4	EN	Enable pin for the IC. Drive this pin high to enable the IC, low to disable. Default high when floating.
5	VOUT	Output voltage pin. Bypass with a 1 μ F ceramic capacitor to GND

DFN1.6x1.6-6 PIN #	NAME	DESCRIPTION
1	VIN	Supply voltage pin. Bypass with a 1 μ F ceramic capacitor to GND
2,5	NC	None connection
3	VOUT	Output voltage pin. Bypass with a 1 μ F ceramic capacitor to GND
4	EN	Enable pin for the IC. Drive this pin high to enable the IC, low to disable. Default high when floating.
6	GND	Ground

TYPICAL CHARACTERISTICS


(Typical values are at $T_A = 25^\circ\text{C}$ unless otherwise specified.)




TYPICAL CHARACTERISTICS (cont')

(Typical values are at $T_A = 25^\circ\text{C}$ unless otherwise specified.)


V_{OUT} Vs. I_{OUT}




V_{OUT} Vs. V_{IN}




V_{OUT} Vs. I_{OUT}




V_{OUT} Vs. V_{IN}



V_{OUT} Vs. I_{OUT}




V_{OUT} Vs. V_{IN}




TYPICAL CHARACTERISTICS (cont')

(Typical values are at $T_A = 25^\circ\text{C}$ unless otherwise specified.)


I_Q Vs. V_{IN}




$V_{DROPOUT}$ Vs. I_{OUT}




$V_{DROPOUT}$ Vs. I_{OUT}




PSRR Vs. Freq.



PSRR Vs. Freq.





PSRR Vs. Freq.




TYPICAL CHARACTERISTICS (cont')

(Typical values are at $T_A = 25^\circ\text{C}$ unless otherwise specified.)



FUNCTIONAL BLOCK DIAGRAM



FUNCTIONAL DESCRIPTION

The ETA5040 family of LDO regulators has been optimized for application in low standby power equipments. The device features 2.5uA ultra-low quiescent current, 45V input voltage and 300mA output current capability.

Enable Sequence

ETA5040 is enabled when all below conditions happen. Otherwise, ETA5040 is in standby mode.

- ◆ EN pin voltage is above Logic High level
- ◆ VIN is higher than Under-Voltage-Lock-Out level.
- ◆ Junction Temperature is not at Over-Temperature Protection level.

Once all above conditions happen, ETA5040 first enables BANDGAP and BIAS. When internal bias is ready, ETA5040 enables LDO core.

ETA5040 is completed forced in shutdown mode when EN pin is below LOGIC_LOW. Otherwise, part only shutdown the VOUT, other circuit is still in operation. Once ETA5040 is in shutdown conditions, Output is discharged by 60Ω resistor (optional).

Output Current Limit and Foldback Current Limit

ETA5040 family features an internal current limit. In normal operation, the ETA5040 limits output current to approximately 400mA. When current limiting engages, the output voltage scales back linearly until the over current condition ends.


In case output is in hard short conditions, ETA5040 also features an internal foldback limit that reduces the output current limit to a lower level, 200mA, then reduce power dissipation ratings of the package.

Over-Temperature Protection

Thermal protection disables the output when the junction temperature rises to approximately 160°C, allowing the device to cool down. When the junction temperature cools to approximately 130°C, the output circuitry is again enabled. Depending on power dissipation, thermal resistance, and ambient temperature, the thermal protection circuit may cycle on and off. This cycling limits regulator dissipation, protecting the device from damage as a result of overheating.


PACKAGE OUTLINE

Package: SOT23-5



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°


Package: DFN1.6x1.6-6



AVAILABLE PART NUMBER

Part Description	Part Number	Package	Mark	Pcs/Reel
2.5V No Discharge SOT23-5	ETA5040V250NS2F	SOT23-5	fdYW	3000
2.5V with Discharge SOT23-5	ETA5040V250DS2F	SOT23-5	ezYW	3000
3.0V No Discharge SOT23-5	ETA5040V300NS2F	SOT23-5	fcYW	3000
3.0V with Discharge SOT23-5	ETA5040V300DS2F	SOT23-5	eyYW	3000
3.3V No Discharge SOT23-5	ETA5040V330NS2F	SOT23-5	feYW	3000
3.3V with Discharge SOT23-5	ETA5040V330DS2F	SOT23-5	faYW	3000
5V No Discharge SOT23-5	ETA5040V500NS2F	SOT23-5	ffYW	3000
5V with Discharge SOT23-5	ETA5040V500DS2F	SOT23-5	fbYW	3000
2.5V No Discharge DFN1.6x1.6-6	ETA5040V250NDCG	DFN1.6x1.6-6	fdYW	3000
2.5V with Discharge DFN1.6x1.6-6	ETA5040V250DDCG	DFN1.6x1.6-6	ezYW	3000
3.0V No Discharge DFN1.6x1.6-6	ETA5040V300NDCG	DFN1.6x1.6-6	fcYW	3000
3.0V with Discharge DFN1.6x1.6-6	ETA5040V300DDCG	DFN1.6x1.6-6	eyYW	3000
3.3V No Discharge DFN1.6x1.6-6	ETA5040V330NDCG	DFN1.6x1.6-6	feYW	3000
3.3V with Discharge DFN1.6x1.6-6	ETA5040V330DDCG	DFN1.6x1.6-6	faYW	3000
5V No Discharge DFN1.6x1.6-6	ETA5040V500NDCG	DFN1.6x1.6-6	ffYW	3000
5V with Discharge DFN1.6x1.6-6	ETA5040V500DDCG	DFN1.6x1.6-6	fbYW	3000

TAPE AND REEL INFORMATION



Device	Package Type	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
ETA5040VXXXQS2F	SOT23-5	5	3000	180	9.5	3.17	3.23	1.37	4	8	Q3
ETA5040VXXXQDCG	DFN1.6x1.6-6	6	3000	180	9.5	1.73	1.73	0.72	4	8	Q1